

BEE III™ Moving Radar System with Automatic Same Direction™ Technology

BEE III is the most compact radar available. It has the smallest detachable display, while retaining larger multicolored windows. BEE III also has the smallest antenna, and it is waterproof. Both pieces can be mounted anywhere in the patrol vehicle.

BEE III is equipped with patented Automatic Same Direction (ASDTM) technology, allowing the versatility of same direction operation without a confusing faster/slower button. The BEE III calculates the speed automatically. In stationary mode, ASD allows you to select a lane of traffic to measure while completely ignoring the other lane.



Features

Benefits

ready to use it. All-black, waterproof antenna housing

makes covert operation easy.

Automatic Same Direction (ASD) mode	• Patented technology eliminates the faster/slower button, freeing up both hands for driving. Measures same direction traffic with computer controlled accuracy.
Directional stationary mode	• Catch a speeder moving in a chosen direction even if there's a closer vehicle moving in the opposite direc- tion.
Fastest target mode	. No more hiding in a semi's shadow.
POP TM technology	• Patent-pending technology can measure traffic speeds without setting off radar detectors.
Tiny display with easy-to-read LED displays	Detachable display unit is small enough to mount anywhere in the vehicle, but has speed windows that are easily distinguished by size, location, and color.
Ergonomic wireless remote control	Each major function has a uniquely-contoured switch, so the radar can be operated without having to look at the remote.
Black equipment housings	. Radar blends into the vehicle's interior until you're

The Company: MPH Industries, Inc. specializes in velocity measurement. Formed in 1975, MPH is one of the largest pliers of Doppler radars to Law Enforcement worldwide. MPH also serves the highway and rail transportation industries, education and sports. MPH Industries is a subsidiary of MPD, Inc., a manufacturer of aerospace components and subsystems, electronic components and breath alcohol analyzers.

Digital signal processing *Reliable, jammer-proof, and maintenance free.*

BEE III™ Directional Traffic Radar

Description: A multi-piece radar with detachable display unit and wireless remote control. The ergonomic design of the remote control ensures comfort, even after hours of use. Each major control function has its own uniquely-contoured switch, so the operator never needs to take his eyes off the road to look at the controls. All minor functions are controlled using unobtrusive, secondary switches on the remote. Unique features include the multi-color display, green for patrol, red for target, and yellow for the lock/fastest window. Same and opposite direction speed-sensing, moving and stationary modes, fastest and strongest target are all included. Automatic Same Direction TM (ASDTM) makes same direction operation simple and removes potential judgment errors. POP feature permits speed measurements without alerting radar detectors.

Special Features

- BEE III is the most compact radar available. It has the smallest detachable display, while retaining large multi-colored speed windows. BEE III has the smallest conical Kaband antenna available, which is also weatherproof. The display and antenna can mount anywhere in any patrol vehicle.
- Patented Automatic Same Direction technology gives you the versatility of same direction operation without a confusing faster/slower button. The BEE III decides whether the target is approaching or receding with 100% accuracy.
- In stationary mode, ASD allows you to select a lane and only measure the targets traveling in that lane, while completely ignoring the traffic in the other lane. Or let the radar measure both lanes and tell you the direction the target is traveling.
- POPTM mode (patent pending) allows the operator to measure the speed of potential violators in stationary mode without setting off a single radar detector.
- Selectable City and Highway modes help minimize shadowing and combining.
- The high-power wireless remote control eliminates a cable while ensuring that the operator doesn't have to point the remote control at the radar. Wired remote optional.
- The reliability and accuracy of the BEE III are guaranteed by MPH Industries, serving law enforcement with products like the Python and K-55 for over twenty-five years.
- BEE III contains the following functions and controls:

Power Range Control Antenna Select
Test Stationary Mode Volume Control
Squelch Patrol Blanking Antenna Standby
Error Detect Same/Opposite Direction Lock/Release
RS-232 Communication Port Fastest Mode

General Specifications

Power: 10.8 to 16.5 Volts DC, 0.9 Amps @ 13.6 V nominal. Fused power cable. Reverse polarity protection.

Speed Range: Stationary:

Speed Display:

Target: 15 to 200 mph Opposite direction moving:

Patrol: 12 to 80 mph in City mode, 20 to 80 mph

(will track to 90 mph) in Highway mode

Target: 15 mph to 200 mph closing speed

Same direction moving:

Patrol: 12 to 80 mph in City mode, 20 to 80 mph

(will track to 90 mph) in Highway mode

Target: \pm 70% of patrol speed (will not measure

speeds within 3 mph of patrol speed)

Target Distance: One mile range typical for an average size vehicle. Range varies with vehicle size,

terrain, weather, and traffic conditions. (Range is lower in same direction mode.) Three LED windows simultaneously display patrol, target, and locked or fastest

play patrol, target, and locked or fastest target speeds. Display brightness automatically adjusts to the ambient light level.

Display Unit Size: $1^{-1/2}$ in. high, 5 in. wide, $2^{-3/4}$ in. deep. Antenna:

Frequency: 33.8GHz ± 100 MHz (Ka-band)

Type: Circularly polarized, with seamless coni-

cal horn and Rexolite microwave lens.

Enclosure: All-aluminum housing with a waterproof

polycarbonate radome cover incorporating

O-ring seals.

Source: Solid state Gunn-effect diode transmitter with

a nominal output power level of 12 to 30 mW.

Power Density: Radiated power is less than 2 mW/cm² at 5

cm. distance from the antenna.

Mixer Diode: Schottky barrier type related for 100 mW

burnout.



MPH Industries, Inc.

316 E. Ninth Street Phone: (888) 689-9222 Owensboro, KY 42303 Fax: (270) 685-6288

